

## DESCRIPTION

### DISK CHANGER

#### 5 TECHNICAL FIELD

[0001] The present invention relates to a disk changer including a plurality of accommodating means for holding a disk such as a CD or a DVD and a disk processing unit that selects one of the accommodating means to load and clamp a  
10 disk to reproduce or record data, and more particularly, to a technology for protecting the disk and the accommodating means. Through the specification, the term "processing" refers to reproducing a disk on which data is recorded or recording data on a disk on which no data is recorded.

15

#### BACKGROUND ART

[0002] A conventional disk player (a disk changer) includes a disk conveying unit that selectively conveys a plurality of trays, each of which accommodates one disk, to  
20 different height positions of a reproducing position, and a disk reproducing unit that reproduces a disk positioned at the reproducing position. The disk reproducing unit includes a clamper, a turn table (a disk table) that clamps a disk together with the clamper, a base that supports the  
25 turn table, and an ascending and descending unit that ascends and descends the base for moving the turn table

between a plurality of height positions and a retracted position. The ascending and descending unit includes a circular cam member that is rotatable about its center and has an inner space and a motor that applies a driving force to the circular cam member. The base is disposed in the space including the center, and a projecting member projecting from the base engages with a cam groove formed on an internally curved face portion of the circular cam member (see, for example, Patent Document 1).

10    [0003]        According to the disk player described in the Patent Document 1, a circular gear portion can sequentially move each of the trays to either one of a reproducing position where a disk is reproduced, a position at a front side from the reproducing position and at a back side of a door, namely, a standby position, and an eject position projected forwardly of the door. An upper tray and a lower tray are placed on an upper sub-tray and a lower sub-tray to be relatively movable in front and back directions, respectively, and first and second pinion gears rotated by a circular gear of the circular gear portion are caused to mesh with the upper sub-tray and the upper tray, and the lower sub-tray and the lower [[sub-]]tray, so that the upper sub-tray and the lower sub-tray are moved in front and back directions according to rotation of the circular gear.

25    [0004]

Patent Document 1: Japanese Patent Application Laid-open No. 2000-100035

DISCLOSURE OF INVENTION

5    PROBLEM TO BE SOLVED BY THE INVENTION

[0005]        ~~However, in the conventional disk changer, a disk conveying unit that selectively conveys a plurality of trays, each of which accommodates a disk, to different height positions of a reproducing position does not include~~  
10 ~~a tray locking mechanism, and includes as a different fixing measure, a mechanism such as a complicated locking unit and an unlocking unit so as not to cause a failure during transportation and operation of the disk changer.~~

[0006]        ~~Further~~ However, since a sub-tray larger than the  
15 tray itself is used for moving the tray from the reproducing position such as an eject position to a far position, and since the large sub-tray is accommodated in the disk changer, efficiency of utilizing space is decreased and the size of the disk changer is increased.

20 [0007]        ~~The present invention has been achieved in view of the above circumstances, and an object of the invention is to provide a disk changer that locks movement of a disk except for a disk to be selected for reproduction or recording.~~

25 [0008]        ~~Another object of the half invention~~ The present invention has been achieved in view of the above

circumstances, and an object of the present invention is to provide a small disk changer by reducing the size of means for moving a disk tray from a reproducing position or a recording position to a far position and performing loading  
5    from the far position.

MEANS FOR SOLVING PROBLEM

[0009]        ~~To solve the above problems and to achieve the object, a disk changer according to one aspect of the present invention includes a plurality of accommodating units for accommodating disks, a selecting unit that selects an accommodating unit from among the accommodating units, a loading mechanism that loads a disk accommodated in the accommodating unit selected by the selecting unit, a~~  
10    ~~disk processing unit that reproduces data from or records data to the disk loaded by the loading mechanism, and a lock mechanism that locks movement of a disk that is not selected by the selecting unit.~~

[0010]        ~~A disk changer~~ To solve the above problems and to  
20    achieve the object, a disk changer according to another aspect of the present invention includes a disk accommodating unit that accommodates a plurality of disk trays, each of the disk trays holding one disk; a disk processing unit that reproduces data from or records data  
25    to a loaded disk; and a loading mechanism that loads a selected disk together with the disk tray from the disk

accommodating unit to a position of the disk processing unit. The loading mechanism includes a tray drawing pinion provided in the disk processing unit; a disk tray that is accommodated in the disk accommodating unit and includes a  
5    tray rack engaged with the tray drawing pinion; and a rack plate that includes a tray drawing rack engaged with the tray drawing pinion, is extendably attached to the disk tray, draws a tray in at a first half process of the loading, and stops the tray at a second half process of the  
10   loading to relay a subsequent drawing to the tray rack.

#### EFFECT OF THE INVENTION

[0011]        With the disk changer according to the present invention, ~~movement of a disk except for a disk to be~~  
15   ~~selected for reproduction or recording can be locked and the disk can be protected regardless of during an operation of the disk changer or during transportation thereof.~~  
Further, the size of the whole disk changer can be reduced.

#### 20    BRIEF DESCRIPTION OF DRAWINGS

[0012]        Fig. 1A is a front view of a cabinet of a disk changer according to an embodiment of the present invention;

              Fig. 1B is a right side view of the cabinet;

25            Fig. 2A is a partially exploded front view of the disk changer;

Fig. 2B is a plan view of the disk changer;

Fig. 3A is a plan view of a rotating mechanism;

Fig. 3B is a plan view of the rotating mechanism;

Fig. 3C is a plan view of the rotating mechanism;

5        Fig. 3D is a plan view of the rotating mechanism;

Fig. 4A is a front view of a tray lock mechanism;

Fig. 4B is a front view of the tray lock mechanism;

Fig. 5A is a front view of a vertical disk tray;

Fig. 5B is a bottom view of the vertical disk tray;

10       Fig. 5C is a right side view of the vertical disk  
tray;

Fig. 5D is a cross section of the vertical disk tray,  
taken along a line A-A shown in Fig. 5A;

Fig. 5E is an enlarged view of a portion C of the  
15       vertical disk tray in Fig. 5D;

Fig. 5F is a cross section of the vertical disk tray,  
taken along a line B-B shown in Fig. 5A;

Fig. 6A is a front view of a first disk tray;

Fig. 6B is a partially exploded front view of a second  
20       disk tray;

Fig. 6C is a partially exploded front view of a third  
disk tray;

Fig. 7A is a schematic for illustrating an actuating  
step of an actuating cam mechanism;

25       Fig. 7B is a schematic for illustrating the actuating  
step of the actuating cam mechanism;

Fig. 7C is a schematic for illustrating the actuating step of the actuating cam mechanism;

Fig. 7D is a schematic for illustrating the actuating step of the actuating cam mechanism;

5            Fig. 7E depicts an actuating step of the actuating step of the actuating cam mechanism;

Fig. 8A is a schematic for illustrating a loading step of the third disk tray;

Fig. 8B is a schematic for illustrating the loading  
10    step of the third disk tray;

Fig. 8C is a schematic for illustrating the loading step of the third disk tray;

Fig. 8D is a schematic for illustrating the loading step of the third disk tray; and

15           Fig. 8E is a schematic for illustrating the loading step of the third disk tray.

#### EXPLANATIONS OF LETTERS OR NUMERALS

[0013]	2a, 2b, 2c	Disk tray (accommodating means)
20	3a, 3b, 3c	Disk
	10	Disk accommodating unit
	21a	Tray rack
	21d	First recess
	30	Rotating mechanism
25	32	Selecting cam
	32b	Cam groove

- 40     Loading mechanism
- 41a, 42a, 43a   Notch
- 42, 43       Rack plate
- 42e, 43e   Tray drawing rack
- 5     43g   Inner projection (locking unit)
- 43h   Outer projection (locking unit)
- 43j   ~~Distal end portion~~ End portion (abutting portion)
- 45     Tray drawing pinion
- 50     Disk reproducing unit
- 10    51a, 52a   Supporting shaft (vertical shafts)
- 52     Tray guide (stopper)
- 52b   Cam pin
- 52c   Guide groove
- 52d   Stopper wall
- 15    52e   Second recess
- 55     Clamp cam
- 55d   Motor
- 60     Lock mechanism
- 61, 62, 63     Cam plate
- 20    61a, 62a, 63a   Lock lever (locking units)

BEST MODE(S) FOR CARRYING OUT THE INVENTION

[0014]       Exemplary embodiments of a disk changer according  
to the present invention will be explained in detail below  
25   with reference to the accompanying drawings. The invention  
will not be limited to the embodiment.



[0015]        Fig. 1A is a front view of a cabinet of a disk  
changer according to an embodiment of the present  
invention; Fig. 1B is a right side view of the cabinet; Fig.  
2A is a partially exploded front view of the disk changer  
5    from which the cabinet has been removed; Fig. 2B is a plan  
view of the disk changer from which the cabinet has been  
removed; Fig. 3A is a plan view of a rotating ~~device~~  
mechanism depicting a state that a first disk tray 2a has  
been selected; Fig. 3B is a plan view of a rotating  
10   mechanism depicting a state that a second disk tray 2b has  
been selected; Fig. 3C is a plan view of the rotating  
mechanism depicting a state that a third disk tray 2c has  
been selected; Fig. 3D is a plan view of the rotating  
mechanism depicting a state that all disk trays have been  
15   locked; Fig. 4A is a front view of a lock mechanism  
depicting a state that the first disk tray 2a has been  
selected and unlocked; and Fig. 4B is a front view of the  
lock mechanism depicting a state that another disk tray has  
been selected and the disk tray 2a has been locked.

20   [0016]        A cabinet 1 is formed in a horizontally long  
rectangular parallelepiped shape with a short depth, a disk  
accommodating unit 10 is provided on a right side, and a  
disk reproducing unit 50, described later, is accommodated  
on a left portion of the cabinet 1 adjacent to the disk  
25   accommodating unit 10. The disk accommodating unit 10 is  
opened at its top portion and a front face portion, and

first, second, and third disks 3a, 3b, and 3c can be taken in and out of disk trays 2a, 2b, and 2c serving as first, second, and third accommodating means of the disk accommodating unit 10. An opening and closing cover 1c  
5 made from transparent resin or semi-transparent resin in an L shape in a side view is attached to an opening via a hinge to pivot upwardly. Since the opening and closing cover 1c is transparent or semi-transparent, a user can see the accommodated disks 3a, 3b, and 3c even if the cover is  
10 closed.

[0017]        As shown in Fig. 2A and Fig. 2B, the disk trays 2a, 2b, and 2c are vertical trays that hold the disks 3a, 3b, and 3c in a vertically lying manner, and lower ends thereof are accommodated in first holding groove 11a,  
15 second holding groove 11b, and third holding groove 11c arranged and formed radially in a tray holder 11 installed in the disk accommodating unit 10, serving as radial lines, so that the disk trays are arranged radially. The disk trays 2b and 2c accommodated in a back side are  
20 accommodated and arranged while being shifted rightward of the disk trays 2a and 2b accommodated at front side predetermined positions (in a direction parallel to or substantially parallel to a disk face). According to the present embodiment, the disk trays are accommodated and  
25 arranged such that center holes 3d of the disks 3b and 3c held in the disk trays 2b and 2c accommodated in the back

side do not overlap with the disks 3a and 3b held in the disk trays 2a and 2b accommodated in the front side.

[0018]        By shifting the disk trays 2b and 2c accommodated in the back side from the disk trays 2a and 2b accommodated  
5    in the front side in a direction parallel or substantially parallel to a disk face, label faces of the disks 3b and 3c accommodated in the back side can be seen and the accommodated disks can be confirmed. By accommodating the disk trays such that the center holes 3d of the disks 3b  
10    and 3c held in the disk trays 2b and 2c accommodated in the back side do not overlap with the disks 3a and 3b held in the disk trays 2a and 2b accommodated and arranged on the front side, most part of the labels can be seen, and also a finger can be inserted into the center holes 3d from the  
15    front sides of the disks 3b and 3c, so that a disk can be attached to and detached from the disk tray without touching a face on which data is written, on a back side of the disk. Since the disk trays 2a, 2b, and 2c are made from transparent resin or semi-transparent resin, a label  
20    face on the far side of the disk trays 2a and 2b can also be seen.

[0019]        A power source switch 1e, a light receiver 1f of a remote controller, a play/pause switch 1g, a stop switch 1h, and a display device 1m for displaying a disk number, a  
25    track number during reproduction, a reproduction elapsing time, and the like are provided on a front panel 1d of the

cabinet 1.

[0020]        Three disk selecting switches 1i, 1j, and 1k  
serving as selecting units, for selecting and reproducing  
one of the disks 3a, 3b, and 3c held in each of the disk  
5    trays 2a, 2b, and 2c are provided on the front panel 1d  
positioned near just below the respective disk trays. The  
disk selecting switches correspond one-to-one to the each  
of the disk trays 2a, 2b, and 2c being accommodated and  
arranged. By thus providing the disk selecting switches 1i,  
10    1j, and 1k, the user can press, without mistake, one of the  
disk selecting switches 1i, 1j, and 1k corresponding to one  
of the disks 3a, 3b, and 3c selected according to its label.

[0021]        The disk reproducing unit 50 will be explained  
next with reference to Fig. 2A and Fig. 2B. A base stand 4  
15    including a top board 4c, four legs 4f, and a standing  
plate 4a provided on a left side in a front view are  
disposed within the cabinet 1. A bracket 4b is attached to  
an upper portion of the standing plate 4a, and shaft holes  
4d and 4e are provided in a left portion of the top board  
20    4c and the bracket 4b, respectively. A tray guide 52  
formed with a guide groove 52c that guides the disk trays  
2a, 2b, and 2c to a position just before the disk  
reproducing unit 50 during loading of a disk is attached to  
a lower portion of a chassis 51 which is formed in a  
25    rectangular shape in a front view of the disk reproducing  
unit 50. Supporting shafts 52a and 51a are provided on a

left and lower portion of the tray guide 52 and a left  
upper portion of the chassis 51. The supporting shafts 52a  
and 51a are fitted into the shaft holes 4d and 4e, so that  
the chassis 51 and the tray guide 52 are integrally and  
5 pivotally supported about the supporting shafts 52a and 51a.  
Positions of the supporting shafts 52a and 51a on a plan  
view are not necessarily at an intersection of extended  
lines of the first holding groove 11a, the second holding  
groove 11b, and the third holding groove 11c as radial  
10 lines, and they can be spaced from the extended lines.

[0022]        A horizontally long D-shaped float base 53 in a  
front view is provided in a hollow portion 51b of the  
chassis 51. The float base 53 is pivotally supported to  
the chassis 51 via pivoting shafts 53a and 53b provided at  
15 the left end thereof, to be pivoted in front and rear  
directions.

[0023]        A disk reproduction unit 54 is attached to the  
float base 53. The disk reproduction unit 54 includes a  
disk table 54b driven by a spindle motor 54a and a pickup  
20 54g that tracks on tracking shafts 54e and 54f by a screw  
shaft 54d driven by a stepping motor 54c to read data on a  
disk. The disk reproduction unit 54 is attached to the  
float base 53 such that a table face of the disk table 54b  
faces a front side.

25 [0024]        A clamp cam 55 formed in an arc shape extending  
along an arc portion 53c of the float base 53 is attached

rightward of the hollow portion 51b of the chassis 51  
movably along the arc portion 53c. An arc-shaped rack 55a  
is formed on an outer periphery of the clamp cam 55, and an  
intermediate small gear 55i meshing with the arc-shaped  
5 rack 55a is provided on the chassis 51. The chassis 51  
includes a gear 55c having a small gear 55b meshing with  
the intermediate small gear 55i. The gear 55c is driven  
through meshing thereof with a small gear 55f of a pulley  
55e belt-driven by a motor 55d provided at a lower portion  
10 of the chassis 51 so that the clamp cam 55 is driven via a  
gear train. A cam groove whose upper portion is inclined  
rearward as seen from a side is formed on the clamp cam 55,  
and cam pins 53d and 53e provided on a right end of the  
float base 53 are fitted in the cam groove, so that, when  
15 the clamp cam 55 is driven by the gear 55c downwardly from  
a state shown in Fig. 2A, the float base 53 is pivoted  
forward about the pivoting shafts 53a and 53b.

[0025]        A tray drawing pinion 45 that meshes with a tray  
drawing rack described later to retract the tray drawing  
20 track toward the disk reproducing unit 50 and that loads  
the disk trays 2a, 2b, and 2c to a position opposing to the  
disk reproducing unit 50 is provided at an end portion of  
the disk accommodating unit 10 of the chassis 51 (the disk  
reproducing unit 50). The tray drawing pinion 45 is driven  
25 by an intermediate gear 44 meshing with the small gear 55b.

[0026]        A clamber supporting plate 55h supporting a

clamper 55g is provided so as to connect an upper portion of the chassis 51 and the tray guide 52 such that a clearance through which the disk trays 2a, 2b, and 2c can pass is provided between the front face of the chassis 51 and the clamper supporting plate 55h. The clamper 55g holds down the disk 3a, 3b, or 3c at its front portion and receives advancement of the disk table 54b due to pivoting of the float base 53, to clamp the disk 3a, 3b, or 3c on the disk table 54b. The clamper 55g is rotated together with the disk table 54b and a clamped disk.

[0027] The rotating mechanism and the tray lock mechanism of the disk reproducing unit 50 will be explained next with reference to Fig. 2A, Fig. 3A to Fig. 3D, Fig. 4A, and Fig. 4B. The rotating mechanism 30 includes a holding frame 31 attached to a lower side of the top board 4c of the base stand 4, a selecting cam 32 with a rectangular shape in a plan view that is held by the holding frame 31 so as to be movable leftward and rightward, a pulley 33 that is held on the holding frame 31 and has a pinion meshing with a rack 32a formed on the selecting cam 32 to move the selecting cam 32 leftward and rightward, and a motor 35 that is held on the holding frame 31 and drives the pulley 33 via a belt 34.

[0028] A cam groove 32b is formed stepwise in the  
25 selecting cam 32, and a cam pin 52b provided at a right  
lower end of the tray guide 52 is fitted into the cam

groove 32b, so that, when the selecting cam 32 moves from left to right, the disk reproducing unit 50 is pivoted about the supporting shafts 52a and 51a from front to back. When the cam pin 52b is positioned inside a first cam groove 32b1, the selecting cam 32 selects the first disk tray 2a and positions the guide groove 52c of the tray guide 52 on an extended line of the holding groove 11a of the tray holder 11. When the cam pin 52b is positioned inside a second cam groove 32b2, the selecting cam 32 selects the second disk tray 2b and positions the guide groove 52c of the tray guide 52 on an extended line of the holding groove 11b of the tray holder 11. When the cam pin 52b is positioned inside a third cam groove 32b3, the selecting cam 32 selects the third disk tray 2c and positions the guide groove 52c of the tray guide 52 on an extended line of the holding groove 11c of the tray holder 11. When the cam pin 52b is positioned inside a fourth cam groove 32b4, the selecting cam 32 is positioned at an all-lock position at which movement of all the trays is locked.

[0029] When the cam pin 52b is positioned inside the cam groove inclined to the moving direction except for the first to the fourth cam grooves, the disk reproducing unit 50 is pivoted from front to back about the supporting shafts 52a and 51a according to movement of the selecting cam 32 from left to right.

[0030] The tray lock mechanism 60 will be explained next.



Cam plates 61, 62, and 63 with a trapezoidal shape in a front view corresponding to each of the disk trays 2a, 2b, and 2c are provided on a right upper face of the selecting cam 32. Lock levers 61a, 62a, and 63a with an "L" shape in  
5 a front view serving as locking units are supported pivotally about pivoting shafts 61b, 62b, and 63b on a bottom plate 11d of the tray holder 11 that is provided on the top board 4c of the base stand 4 positioned on the disk accommodating unit 10 and holds the disk trays 2a, 2b, and  
10 2c during accommodation. The lock levers 61a, 62a, and 63a are biased in a counterclockwise direction in a front view by leaf springs (not shown) attached to the bottom plate 11d, and respective lock pins 61c, 62c, and 63c are normally engaged with notches 41a, 42a, and 43a formed on  
15 lower edges of first, second, and third rack plates 41, 42, and 43, described later, attached to the first, the second, and the third disk trays 2a, 2b, and 2c slide-moving on the bottom plate 11d of the tray holder 11, so that movement of the disk trays 2a, 2b, and 2c are locked.

20 [0031]        As shown in Fig. 3A, when the cam pin 52b is positioned within the cam groove 32b1, the disk reproducing unit 50 is positioned to face the first disk tray 2a. At that time, the cam plate 61 presses up a left end of the lock lever 61a to disengage the notch 41a and the lock pin  
25 61c from each other to unlock the first disk tray 2a, thereby allowing loading of the first disk tray 2a to a

position of the disk reproducing unit 50.

[0032]        As shown in Fig. 3B, when the cam pin 52b is positioned within the cam groove 32b2, the disk reproducing unit 50 is positioned to face the second disk tray 2b. At that time, the cam plate 62 presses up a left end of the lock lever 62a to disengage the notch 42a and the lock pin 62c from each other to unlock the second disk tray 2b, thereby allowing loading of the second disk tray 2b to the position of the disk reproducing unit 50.

[0033]        As shown in Fig. 3C, when the cam pin 52b is positioned within the cam groove 32b3, the disk reproducing unit 50 is positioned to face the third disk tray 2c. At that time, the cam plate 63 presses up a left end of the lock lever 63a to disengage the notch 43a and the lock pin 63c from each other to unlock the third disk tray 2c, thereby allowing loading of the third disk tray 2c to the position of the disk reproducing unit 50. By thus locking movement of a disk which has not been selected, the disks and the disk trays can be protected during an operation of the disk changer.

[0034]        As shown in Fig. 3D, when the cam pin 52b is positioned within the lock groove 32b4, the disk reproducing unit 50 is positioned at a lock position where movement of all of the disk trays 2a, 2b, and 2c are locked. At that time, all the cam plates 61, 62, and 63 are released from the left ends of all the lock levers 61a, 62a,

and 62c, and all the notches 41a, 42a and 43a and all the lock pins 61c, 62c, and 63c are engaged with each other, so that movement of all of the disk trays 2a, 2b, and 2c are locked. By thus locking movement of all the disk trays, the disks and the disk trays can be protected during transportation of the disk changer.

[0035] Since the lock groove 32b4 for locking movement of all of the disk trays 2a, 2b, and 2c is provided in the cam groove 32b, all of the disk trays 2a, 2b, and 2c are  
10 locked by positioning the cam pin 52b in the lock groove 32b4 during product transportation and the like, so that adverse influence such as damage of a disk tray itself or damage to surrounding parts due to movement during transportation can be prevented.

15     [0036]     A structure of a vertical tray will be explained  
next with reference to Fig. 5A to Fig. 5F. Fig. 5A is a  
front view of the vertical tray; Fig. 5B is a bottom view  
of the vertical tray; Fig. 5C is a right side view of the  
vertical tray; Fig. 5D is a cross section of the vertical  
20   tray, taken along a line A-A shown in Fig. 5A; Fig. 5E is  
an enlarged view of a portion C of the vertical tray shown  
in Fig. 5D; and Fig. 5F is a cross section of the vertical  
tray, taken along a line B-B shown in Fig. 5A.

[0037] In the above explanation, while the disk trays  
25 are explained as the first, the second, and the third disk  
trays 2a, 2b, and 2c corresponding to the first, the second,

and the third disks 3a, 3b, and 3c, since shapes of the first, the second, and the third disk trays 2a, 2b, and 2c are the same, these trays are collectively explained below as a vertical tray 20.

5    [0038]        The vertical tray 20 includes a back plate 21 that faces a back face (data face) of a disk to be held and supports the disk, a front plate 22 that is fixed on a lower front side of the back plate 21 via a clearance 27 larger than a thickness of the disk, whose upper edge 22a  
10 is formed in an arc shape facing downwardly, and that overlaps with a lower outer periphery of the disk accommodated in the clearance 27 at the upper edge 22a, and supports the disk from a label face side thereof, and disk supporting members 23 and 24 that are arranged between the  
15 back plate 21 and the front plate 22 to connect therebetween, and support the disk from the lower side in a vertical direction. The back plate 21 and the front plate 22 constitute disk holding faces.

[0039]        The back plate 21 has a face that faces a lower  
20 portion positioned below a disk center and a right side portion of a back face of the accommodated disk but does not have a face that faces another portion of the back face. A tray rack 21a for loading the vertical tray 20 to a position of the disk reproducing unit 50 is formed on a  
25 lower back face of the back plate 21, an elongated mounting hole 21b for mounting first, second, and third rack plates,

described later, is formed on a lower side of the tray rack 21a, and a recess 21d engaging with a locking unit of the rack plate is formed on an upper left side of the mounting hole 21b. An arc-shaped strip portion 21c facing an outer  
5 periphery of a back face of an accommodated disk is formed in an inclined face (becoming higher) approaching to the disk as it approaches to an outer periphery thereof, and when a disk is accommodated, only an outermost periphery of the back face of the disk contacts with the back plate 21  
10 while a data region at the inner side of the outermost periphery of the disk is put in a floating state from the back plate 21, so that the data region is prevented from being damaged due to contact with the back plate 21.

[0040]        The disk supporting member 23 is formed in an arc  
15 piece shape, and it is disposed in the clearance 27 between the front plate 22 and the back plate 21 along a right portion of the arc-shaped upper edge 22a of the front plate 22. The disk supporting member 24 is formed in a triangle plate shape and it is disposed in the clearance 27 between  
20 the front plate 22 and the back plate 21 such that one side of the disk supporting member 24 extends along a left portion of the arc-shaped upper edge 22a of the front plate 22. Edge portions 23a and 24a serving as disk supporting portions and abutting on lower left and right portions of  
25 an outer peripheral edge of an accommodated disk, the lower and right portions being positioned below a center position

of the accommodated disk, to support the disk vertically  
are formed on upper end inner portions of the disk  
supporting members 23 and 24. The edge portions 23a and  
24a support a disk by having an outer peripheral edge of  
5 the disk placed thereon.

[0041]        Fig. 5A depicts height positions of a disk D1 put  
during accommodation thereof in the vertical tray 20 and of  
a disk D2 which has been clamped by the disk table 54b  
during reproduction. The downward arc-shaped upper edge  
10 22a of the front plate 22 overlaps with a lower outer  
periphery of the disk D1 during accommodation and it is  
formed in an arc shape approximately concentric to an outer  
peripheral edge of the disk during reproduction such that  
it is equally spaced from the outer peripheral edge of the  
15 disk D2 clamped and moved upwardly during the reproduction.

[0042]        An upward inclined face 25a and two left and  
right projections 25 and 25 for guiding the lower outer  
periphery of the accommodated disk D1 to approach to the  
front plate 22 are provided on an outer periphery of the  
20 arc-shaped strip portion 21c of the back plate 21  
positioned below the edge portions 23a and 24a serving as  
two left and right disk supporting portions.

[0043]        Two projections 26 and 26 for pushing the lower  
outer periphery of the accommodated disk D1 toward the back  
25 plate 21 to incline the disk D1 backward are provided on  
left and right portions of the back face of the front plate

22 positioned below the edge portions 23a and 24a,  
positioned above the projections 25 and 25, and positioned  
near the upper edge 22a. With the above configuration, the  
vertical tray 20 holds the disk D1 such that the disk is  
5 put vertically and inclined backward. By holding the disk  
D1 in a backward inclined state, even if the vertical tray  
20 is vibrated in front and rear directions, the disk D1  
will not tilt forward to drop off from the vertical tray 20.  
[0044]        The loading mechanism for a disk will be  
10 explained next with reference to Fig. 6A to Fig. 6C, Fig.  
7A to Fig. 7E, and Fig. 8A to Fig. 8E. Fig. 6A is a front  
view of a first disk tray including a first rack plate; Fig.  
6B is a partially exploded front view of a second disk tray  
including a second rack plate; Fig. 6C is a partially  
15 exploded front view of a third disk tray including a third  
rack plate; Fig. 7A to Fig. 7E are enlarged views of a  
portion B in Fig. 2A depicting actuating steps of an  
actuating cam mechanism for starting loading; and Fig. 8A  
to Fig. 8E are cross sections taken along a line A-A shown  
20 in Fig. 2A depicting loading steps of the third disk tray  
including the third rack plate.

[0045]        The laterally elongated rectangular plate-shaped  
first rack plate 41 is mounted on a back face of a lower  
portion of the first disk tray 2a held in the first holding  
25 groove 11a of the tray holder 11 by inserting two mounting  
pins 41b and 41c into the mounting hole 21b of the disk

tray 2a. A lower edge 41d of the rack plate 41 is positioned below the lower edge of the disk tray 2a and the lower edge 41d is supported on the bottom plate 11d of the tray holder 11, so that the disk tray 2a attached with the rack plate 41 slides and moves on the bottom plate 11d  
5 along the holding groove 11a.

[0046]        The notch 41a is formed on the lower edge 41d of the rack plate 41, and the lock pin 61c of the lock lever 61a is engaged with the notch 41a. A first tray drawing  
10 rack 41e is formed on an upper edge of the first rack plate 41, and the first tray drawing rack 41e is formed such that a length and a height thereof completely conform to those of the tray rack 21a. A left end portion 41i of the first rack plate 41 is positioned to conform to a left end  
15 portion of the disk tray 2a and a right end portion thereof projects rightward from a right end portion of the disk tray 2a. The two mounting pins 41b and 41c of the first rack plate 41 are positioned at left and right ends of the mounting hole 21b of the disk tray 2a, respectively. A  
20 circular hole 41f is provided above a left end of the mounting hole 21b, and an elongated hole 41g is provided above a right end of the mounting hole 21b. Pins 41h and 41i fitted into the circular hole 41f and the elongated hole 41g, respectively, are provided in the first rack  
25 plate 41. The pin 41h is fitted into the circular hole 41f and the pin 41i is fitted into the elongated hole 41g so



that the first rack plate 41 is fixed so as not to extend and retract leftward and rightward with respect to the disk tray 2a. Thus, since the disk tray 2a and the rack plate 41 do not extend and retract, it is unnecessary to

5 manufacture them as separate members so that the disk tray 2a and the rack plate 41 can be formed as a single disk tray 2a integrally.

[0047]        The laterally elongated rectangular plate-shaped second rack plate 42 is mounted on a back face of a lower  
10 portion of the second disk tray 2b held in the second holding groove 11b of the tray holder 11 by inserting two mounting pins 42b and 42c into the mounting hole 21b of the disk tray 2b. A lower edge 42d of the rack plate 42 is positioned below the lower edge of the disk tray 2b and the  
15 lower edge 42d is supported on the bottom plate 11d of the tray holder 11, so that the disk tray 2b attached with the rack plate 42 slides and moves on the bottom plate 11d along the holding groove 11b.

[0048]        The notch 42a is formed on the lower edge 42d of  
20 the rack plate 42, and the lock pin 62c of the lock lever 62a is engaged with the notch 42a. A second tray drawing rack 42e is formed on an upper edge of the second rack plate 42, and the second tray drawing rack 42e is formed such that a height shape thereof conforms to that of the  
25 tray rack 21a. The second rack plate 42 can extend and retract leftward and rightward with respect to the disk

tray 2b, and it extends and retracts by a distance L2 from the maximum extended state shown in Fig. 6B where the mounting pin 42b is positioned at the left end position of the mounting hole 21b to a position where the mounting pin 42c reaches the right end position of the mounting hole 21b. The second tray drawing rack 42e is formed from the left end portion 42j of the rack plate 42 to a length of R2.

[0049]        When the second rack plate 42 is in the maximum extended state, approximately half length of the second rack plate 42 overlaps with the disk tray 2b. The second tray drawing rack 42e is formed from the left end portion 42j of the rack plate 42 to the length of R2, described later. A laterally elongated "U" shaped slit is formed near the right of center of the second rack plate 42, and an inner projection 42g and an outer projection 42h are formed on a front face and a back face of a distal end of a flexure piece 42f formed so as to be surrounded by the slit, respectively. The inner projection 42g is engaged with the recess 21d (see Fig. 8A) serving as a first recess provided in the disk tray 2b at the maximum extended position shown in Fig. 6B by a spring force of the flexure piece 42f. The inner projection 42g and the outer projection 42h constitute a locking unit. A rectangular rack plate 42i attached to a left end of the rack plate 42 is used for increasing the thickness of the rack plate 42 to prevent the rack plate 42 from rattling in the holding groove 11c

or the guide groove 52c (see Fig. 8A).

[0050]        A laterally elongated rectangular plate-shaped  
third rack plate 43 is mounted on a back face of a lower  
portion of the third disk tray 2c held in the third holding  
5 groove 11c of the tray holder 11 by inserting two mounting  
pins 43b and 43c into the mounting hole 21b of the disk  
tray 2c. A lower edge 43d of the rack plate 43 is  
positioned below the lower edge of the disk tray 2c and the  
lower edge 43d is supported on the bottom plate 11d of the  
10 tray holder 11, so that the disk tray 2c attached with the  
rack plate 43 slides and moves on the bottom plate 11d  
along the holding groove 11c. The notch 43a is formed at  
the lower edge 43d of the rack plate 43, and the lock pin  
63c of the lock lever 63a engages with the notch 43a.

15 [0051]        A third tray drawing rack 43e is formed on an  
upper edge of the third rack plate 43, and the third tray  
drawing rack 43e is formed such that a height shape thereof  
coincides with that of the tray rack 21a. The third rack  
plate 43 can extend and retract leftward and rightward with  
20 respect to the disk tray 2c, and extends and retracts by a  
distance L3 from the maximum extended state shown in Fig.  
6C where the mounting pin 43b is positioned at the left end  
position of the mounting hole 21b to a position where the  
mounting pin 43c reaches the right end position of the  
25 mounting hole 21b. The third tray drawing rack 43e is  
formed from the left end portion 43j of the rack plate 43

to a length of R3, described later.

[0052]        A laterally elongated "U"-shaped slit is formed on a right side of the third rack plate 43, and an inner projection 43g and an outer projection 43h are formed on  
5 front and back faces of a distal end of the flexure piece 43f formed so as to be surrounded by the slit, respectively. The inner projection 43g engages with the recess 21d serving as a first recess provided in the disk tray 2c at the maximum extended state shown in Fig. 6C by a spring  
10 force of the flexure piece 43f. The inner projection 43g and the outer projection 43h constitute a locking unit. A rectangular rack plate 43i attached at a left end of the rack plate 43 is used for increasing the thickness of the rack plate 43 to prevent the rack plate 43 from rattling in  
15 the holding groove 11c or the guide groove 52c (see Fig. 8A). Loading distances from the first, the second, and the third disk trays 2a, 2b, and 2c to the disk reproducing unit 50 are different.

[0053]        Actuating steps of the actuating cam mechanism  
20 that starts loading of a disk will be explained next with reference to Fig. 7A to Fig. 7E. As shown in Fig. 2B, when the first, the second, and the third disk trays 2a, 2b, and 2c are respectively held in the first holding groove 11a, the second holding groove 11b, and the third holding groove  
25 11c of the tray holder 11 and accommodated in the tray holder 11, left end portions 41j, 42j, and 43j of the rack

plates 41, 42, and 43 are positioned at the left end  
portion of the tray holder 11, respectively.

[0054]        When any one of the disk selecting switches 1i,  
1j, and 1k is selected to be turned ON, the disk  
5 reproducing unit 50 is pivoted to position the guide groove  
52c of the tray guide 52 on an extended line of selected  
one of the holding grooves 11a, 11b, and 11c of the tray  
holder 11. When the disk reproducing unit 50 is pivoted to  
position the tray drawing pinion 45 to face any one of the  
10 left end portions 41j, 42j, and 43j of the rack plates 41,  
42, and 43, the tray drawing pinion 45 does not mesh with  
the tray drawing racks 41e, 42e, and 43e of the rack plates  
41, 42, and 43 or the tray rack 21a.

[0055]        The actuating cam mechanism 70 has a function of  
15 drawing the rack plate 41, 42, or 43, or the single disk  
tray 2a toward the disk reproducing unit 50 to cause it to  
mesh with the tray drawing pinion 45 at a loading start  
time of selected one of the disks 3a, 3b, and 3c.

[0056]        The actuating cam mechanism 70 is provided at an  
20 end of the disk reproducing unit 50 near the disk  
accommodating unit 10, and includes an actuating rack 71a  
meshing with the tray drawing pinion 45, and a cam pin 71  
moving downward (in a direction crossing a disk tray  
drawing direction) by rotation of the tray drawing pinion  
25 45.

[0057]        The actuating cam mechanism 70 includes a cam

groove 72 having an opening 72a formed on a back side of  
the first, the second, and the third rack plates 41, 42,  
and 43 or the single disk tray 2a and formed above the left  
end portions 41j, 42j, and 43j, a right inclined groove 72b  
5 continuous to the opening 72a, and a horizontal groove 72c.

[0058]        The actuating steps of the actuating cam  
mechanism 70 that starts loading of a disk will be  
explained with reference to Fig. 7A to Fig. 7E. A first  
step shown in Fig. 7A is a standby state. At a second step  
10 shown in Fig. 7B, the actuating rack 71a is pressed down by  
rotation of the tray drawing pinion 45 so that the cam pin  
71 engages with the opening 72a of the cam groove 72. At a  
third step shown in Fig. 7C, the cam pin 71 is further  
pressed down to move downward within the right inclined  
15 groove 72b and draw the rack plates 41, 42, and 43 leftward  
(toward the disk reproducing unit 50).

[0059]        At a fourth step shown in Fig. 7D, when the cam  
pin 71 reaches the horizontal groove 72c, the tray drawing  
pinion 45 meshes with the tray drawing rack 41e, 42e, or  
20 43e or the tray rack 21a and meshing between the actuating  
rack 71a and the tray drawing pinion 45 is released. At a  
fifth step shown in Fig. 7E, the tray drawing rack 41e, 42e,  
or 43e or the tray rack 21a is drawn in the disk  
reproducing unit 50 by the tray drawing pinion 45, and the  
25 cam pin 71 is relatively moved rightward within the  
horizontal groove 72c. Thus, the tray drawing pinion 45

and the tray drawing rack 41e, 42e, or 43e (the rack plate 41, 42, or 43) or the tray rack 21a that does not mesh with each other at a loading start time can be caused to mesh with each other by the actuating cam mechanism 70 without  
5 causing teeth of the pinion and teeth of the rack to strike against each other.

[0060]        Loading steps of the third disk tray 2c including the third rack plate 43 will be explained next with reference to Fig. 8A to Fig. 8E. With reference to Fig. 8A,  
10 the third disk tray 2c attached with the third rack plate 43 is held in the third holding groove 11c of the tray holder 11 provided in the disk accommodating unit 10. The disk tray 2c and the rack plate 43 are locked in the maximum extended state by engagement of the inner  
15 projection 43g of the flexure piece 43f of the rack plate 43 with the recess 21d (the first recess) of the disk tray 2c.

[0061]        The left ~~distal~~ end portion 43j of the rack plate 43 constitutes an abutting portion where it abuts on a  
20 stopper wall 52d serving as a stopper provided in the guide groove 52c of the tray guide 52 to stop movement of the rack plate 43, and it is positioned at a left end of the tray holder 11 during accommodation of the disk tray 2c.  
P1 indicates a disk center position during accommodation,  
25 P2 indicates a position of the tray drawing pinion 45, and  
P3 indicates a position of the disk table 54b, namely, the

• • • •

• • • •

• • • •



disk tray 2c still meshes with the tray drawing pinion 45,  
thereby receiving a driving force from the pinion 45. The  
inner projection 43g serving as the locking unit is pushed  
out of the recess 21d serving as the first recess and the  
5 outer projection 43h serving as the locking unit is pushed  
into the recess 52e serving as the second recess and  
provided in the guide groove 52c, thereby unlocking the  
rack plate 43 from the disk tray 2c.

[0064]      At the fifth step shown in Fig. 8E, only the disk  
10 tray 2c is conveyed leftward to the position of the disk  
table 54b, namely, the loading position P3. That is, the  
rack plate 43 draws the disk tray 2c in, in a first half  
process of loading and it stops in a second half process  
thereof for the tray rack 21a to continue the subsequent  
15 drawing. A movement distance L3 of only the disk tray 2c  
shown in Fig. 8D corresponds to an extending and retracting  
distance L3 of the rack plate 43 and the disk tray 2c shown  
in Fig. 6C.

[0065]      Loading of the second disk tray 2b including the  
20 second rack plate 42 is performed by utilizing the cam pin  
71 as a stopper and a terminal end of the horizontal groove  
72c of the rack plate 42 as an abutting portion similarly  
to the third disk tray 2c. By reducing the size of means  
for moving the disk trays 2b and 2c to a position far from  
25 the disk reproducing unit 50 to perform loading at the far  
position as the laterally elongated rectangular plate-

shaped rack plates 42 and 43 extendably and retractably attached to the disk trays 2b and 2c by utilizing sub-trays or the like, the disk changer can be reduced in size.

[0066]        While the embodiment of the present invention has  
5    been explained above, the disk changer of the present invention is also applicable to a horizontal disk changer in which a disk is placed in a lying state, as well as to the vertical disk changer in which the disk is placed in a vertically standing state. The disk changer of the present  
10   invention is also applicable to a disk changer in which a disk reproducing unit is parallelly translated such as the one disclosed in Patent Document 1 (Japanese Patent Application Laid-Open No. 2000-100035). The disk changer of the present invention is applicable to a data recording  
15   device that records data in a disk, as well as the disk reproducing device.

#### INDUSTRIAL APPLICABILITY

[0067]        As described above, since the disk changer  
20   according to the present invention includes the lock mechanism that locks movement of a disk except for during reproduction from or recording in a disk, it is useful as a disk changer that can protect the disk regardless of during an operation or transportation.